



# PTFE-TAPE PROFESSIONAL

## PTFE TAPE FOR SEALING METAL AND SYNTHETIC THREADED CONNECTIONS.



### TECHNICAL SPECIFICATIONS

**Chemical base:** PTFE

**Colour:** White

### STORAGE CONDITIONS

A minimum of 24 months. Store in properly sealed packaging in a dry place at between +5°C and +25°C.

### PRODUCT DESCRIPTION

PTFE tape for sealing metal and synthetic threaded connections.

### FIELD OF APPLICATION

For sealing metal and synthetic threaded connections. Suitable for water, oxygen, steam, fuels, solvents and acids. Not suitable for gas.

### PROPERTIES

- 100% PTFE
- Chemical resistant
- Mould resistant
- UV resistant
- Removable
- Immediately loadable

### PREPARATION

**Preliminary surface treatment:** Thoroughly clean and degrease surfaces.

### APPLICATION

#### Directions for use:

Apply the tape tightly in the direction of the thread, towards the end of the thread, while allowing a 50% overlap. Assemble the connection and do not turn backward to avoid damaging the tape.

### TECHNICAL PROPERTIES

**Water resistance:** Very good

**Temperature resistance:** -200°C to +260°C.

**Chemicals resistance:** Very good.