



RIPARA METALLO

IRONCLAD DUAL-COMPONENT EPOXY PUTTY FOR METAL.



PRODUCT DESCRIPTION

Dual-component epoxy putty for permanent repair and restoration of metal objects.

FIELD OF APPLICATION

For repairing metal objects. For numerous repairs in and around the home, car, boat and caravan, machines and tools. Fill cracks and holes. Can be used indoors and outdoors. Tip: Can also be used as a mouldable plug to fill screw holes.

PROPERTIES

- Fast
- Paintable
- Easy to apply
- No shrinkage
- All-weather resistant
- Sandable

PREPARATION

Working conditions: Use only at temperatures between +15°C and +25°C.

Personal safety: Preferably, process with gloves. After use, wash hands immediately and thoroughly with soap and water.

Preliminary surface treatment: The surface must be properly sanded and then cleaned and degreased.

Tools: A moist knife to cut off the required amount from the stick.

APPLICATION

Directions for use:

Cut the required quantity from the rod with a damp knife (reinsert foil). Knead with your fingers until a homogeneous colour is obtained. If kneading is difficult, bring the rod at room temperature. Apply within 3-4 minutes after mixing and put into shape. Cut off excess mass with a knife. Remove fingerprints by rubbing with water or a damp cloth before curing starts.

Stains/residue: Remove fingerprints by rubbing with water or a damp cloth before curing starts.

TECHNICAL PROPERTIES

Moisture resistance: Very good

UV resistance: Good

Filling capacity: Very good

TECHNICAL SPECIFICATIONS

Colour: Grey

Viscosity: approx. 0 mPa.s.

Solid matter: approx. 100 %

STORAGE CONDITIONS

At least 18 months after production. Limited shelf life after opening. Store in a dry, cool and frost free place.