



# RIPARA SOTT'ACQUA

## ROCK SOLID DUAL-COMPONENT EPOXY PUTTY.



### PRODUCT DESCRIPTION

Dual-component epoxy putty for permanent repair and restoration of articles that are exposed to vapours or water.

### FIELD OF APPLICATION

For repairing objects that are exposed to vapours or water. For numerous repairs in and around the home, car, boat and caravan. Ideal for marine applications and emergency repairs under water. Fill cracks and holes. Can be used indoors and outdoors. Tip: Can also be used as a mouldable plug to fill screw holes. Not suitable for Polyethylene (PE), polypropylene (PP), PTFE.

### PROPERTIES

- Fast
- Paintable
- Easy to apply
- No shrinkage
- Applicable under water
- Sandable

### PREPARATION

**Working conditions:** Use only at temperatures between +15°C and +25°C.

**Personal safety:** Preferably, process with gloves. After use, wash hands immediately and thoroughly with soap and water.

**Preliminary surface treatment:** The surface must be properly sanded and then cleaned and degreased.

**Tools:** A moist knife to cut off the required amount from the stick.

### APPLICATION

#### Directions for use:

Cut the required quantity from the rod with a damp knife (reinsert foil). Knead with your fingers until a homogeneous colour is obtained. If kneading is difficult, bring the rod at room temperature. Apply within 3-4 minutes after mixing and put into shape. Cut off excess mass with a knife. Remove fingerprints by rubbing with water or a damp cloth before curing starts.

**Stains/residue:** Remove fingerprints by rubbing with water or a damp cloth before curing starts.

### TECHNICAL PROPERTIES

**Water resistance:** Very good

**UV resistance:** Good

**Filling capacity:** Very good

### TECHNICAL SPECIFICATIONS

**Colour:** Beige

**Viscosity:** approx. 0 mPa.s.

**Solid matter:** approx. 100 %

### STORAGE CONDITIONS

At least 18 months after production. Limited shelf life after opening. Store in a dry, cool and frost free place.