



RIMUOVI SILICONE

FOR THOROUGHLY REMOVING CURED SILICONE SEALANT RESIDUES



Points of attention: The treatment with Bostik Rimuovi Silicone may need to be repeated in some cases.

May cause staining on some metals, porous materials and painted wood. In this case, first do a test on a less visible place.

TECHNICAL SPECIFICATIONS

Chemical base: Mineral oil.

Colour: Brown

Viscosity: approx. 0 mPa.s., Thixotropic

Density: approx. 0.8 g/cm³

STORAGE CONDITIONS

At least 24 months after date of manufacture. Store in properly sealed packaging in a dry place at between +5°C and +25°C.

PRODUCT DESCRIPTION

For thoroughly removing cured silicone sealant residues in joints and on substrates. Safe to use without damage. Can be used on ceramic tiles, glass, metal, synthetics, laminates, aluminium and enamels.

FIELD OF APPLICATION

Suitable for thoroughly removing cured silicone sealant residues in joints and on substrates. Can be used on ceramic tiles, glass, metal, synthetics, laminates, aluminium and enamels. Not suitable for nylon.

PROPERTIES

- Safe to use without damage
- With brush in cap
- Easy to apply
- Thorough effect

PREPARATION

Working conditions: Do not use in temperatures $\leq +5^{\circ}\text{C}$.

Surface requirements: The surface must be completely dry and clean, both before and during treatment.

APPLICATION

Directions for use:

Stir thoroughly before using. Cut away the existing silicone sealant as much as possible. Apply the paste generously on the silicone residue. Allow to act for at least 30 minutes. Clean with a dry cloth. If necessary, repeat the treatment.

Degrease the surface thoroughly with, e.g. methylated spirits prior to the application of the new silicone sealant.